

MATERIALS CHARACTERIZATION CAPABILITIES

The Materials Characterization Laboratory consists of thermal analysis, mechanical, and spectroscopic characterization facilities. The laboratory is used to establish the basic molecular and microstructure of materials as well as the thermal, optical and electronic macroscopic properties. Key equipment includes a comprehensive thermal analysis facility including NETZSCH, Mettler Toledo, and TA Instruments equipment. The facility contains the latest version of standard thermal analysis equipment such as DSC, TGA, DMA, TMA, and Parallel Plate Rheology, as well as some specialized equipment such as Mettler Toledo's Flash DSC.

Testing Capabilities

Rheology Testing

Rheology is used to determine minimum viscosity, pot life and viscosity change during resin curing.

Differential Scanning Calorimetry

DSC is used to determine glass transition of cured composites, optimize time-temperature cure cycles and determine the kinetics of reaction.

Thermogravimetric Analysis

TGA is used to determine volatiles, resin and fiber content of composites and prepregs.

Light Flash Thermal Diffusivity

Thermal diffusivity is a measure of the consolidation of the fiber and resin of a composite. Higher consolidation yields higher thermal diffusivity.

Dynamic Mechanical Analysis

DMA is used to determine the glass transition temperature for polymers and composites as well as changes in modulus as a function time and temperature.

Fourier Transform Infrared Spectroscopy

FTIR analyzes the chemical functional groups present in a prepreg or composite. The system at CCM can carry out measurements in the near and mid IR wavelength regions. Samples can be transmission and reflection modes.

Hot Stage - Video Microscopy

This equipment allows one to observe transient changes in the sample such as: bubble formation, color change (from decomposition), and motion due to stress relaxation as a function of time and temperature.

DiaStron Single Fiber Tension Tester

This system automates the testing of single filaments of high performance fibers for determination of tensile strength, modulus and strain at failure is used for the calculation.



Equipment

- NETZSCH Differential Scanning Calorimeter (DSC)
- NETZSCH Thermogravimetric Analyzer (TGA)
- NETZSCH Light Flash Thermal Diffusivity
- NETZSCH Advanced Kinetics Software
- NETZSCH Thermomechanical Analyzer (TMA)
- NETZSCH High Pressure DSC (HPDSC)
- METTLER DSC
- METTLER Flash DSC
- METTLER TGA/DSC
- METTLER Dynamic Mechanical Analyzer (DMA)
- METTLER Hotstage-Video Microscopy
- METTLER XP2U Balance Sensitivity 0.1µg
- Perkin Elmer – FTIR Spectrometer with Microscope
- TA Instruments DHR Rheometer
- TA Instruments AR 2000 Rheometer
- DiaStron Single Fiber Tension Tester

PIONEERING INNOVATION EXCELLENCE

SINCE 1974

Technical Contacts:

Joseph Deitzel, Ph.D.
jdeitzel@udel.edu

Steve Sauerbrunn, Ph.D.
sauerbru@udel.edu

101 Academy Street
Newark, DE 19716